

Stellana Skid Steer Tires

Resilient Tire

Our skid steer tires are characterized by their grip, stability, substantial load tolerance, tear-resistance, and comfort.



Key Attributes:

- Multi-layer construction
- High performance tread
- Reduced heat build up
- Exceptional wear characteristics
- High driver comfort



Increase Your Productivity and Reduce Downtime

Available in both smooth and self-cleaning traction treads, our skid steer tires are constructed from locally sourced, high-quality rubber. Every aspect of these tires has been engineered to provide unparalleled strength and stability without sacrificing the smooth, cushioned ride found in a pneumatic tire.

The skid steer tire construction includes a heavy-duty sidewall to prevent cutting and tearing and bead reinforcements for added strength. Characterized by its grip, stability, substantial load tolerance, and tear resistance, this tire can handle the roughest terrains while providing a comfortable ride. Unlike standard pneumatic tires, our heavy-duty solid skid steer tires eliminate the unanticipated downtime that results from punctured or flat tires.



Key Attributes


- Enhanced longevity with substantially increased wear resistance when compared to a pneumatic tire – zero downtime.
- Varying tread depths and patterns to handle all terrains.
- Cut resistant smooth and self-cleaning traction treads.
- Aperture (sidewall hole) designs available for a smooth, cushioned ride.
- Configurations with or without rims available.
- Heavy-duty sidewall and reinforced base.

Available Tire Sizes

				Actual Tire Dimensions		Load Capacity	
Tire Size	Rim Size	Tread Option	Cushion Option	Overall Diameter [mm] [in]	Overall Width [mm] [in]	10 km/h [kg]	6 mph [lb]
31x10-16	6.00-16	Traction/Smooth	Aperture/Plain	785 30,9	252 9,9	3480	7700
31x10-20	7.50-20	Traction/Smooth	Aperture/Plain	785 30,9	252 9,9	3660	8100
33x12-20	7.50-20	Traction/Smooth	Aperture/Plain	835 32,9	287 11,3	4720	10400
33x12-20	8.00-20	Traction/Smooth	Aperture/Plain	835 32,9	287 11,3	4720	10400



With or without rim



Durable multi-layer construction